

Passive 10X Voltage Probe

TPP0051 Datasheet



TPP0051 Passive Voltage Probe

The TPP0051 probe is for use on BNC oscilloscopes with 1 M Ω /20 pF inputs.

Key performance specifications

- 10X attenuation
- 50 MHz bandwidth
- 1.3 m length
- UL61010-031; 2007, CAN/CSA C22.2 No. 61010-031-07, IEC61010-031; IEC 61010-031/A1:2008

Applications

- Low-frequency measurements
- Low-frequency computer and telecom measurements
- Power supplies
- Low-frequency amplifiers

Specifications

All specifications are guaranteed unless noted otherwise. All specifications apply to all models unless noted otherwise.

Electrical characteristics

Bandwidth	DC to 50 MHz
Rise time	<7 ns (typical)
Compensation range	15 pF to 25 pF
Input resistance	10 M Ω \pm 1.5%
Input capacitance	<12 pF (typical)
Propagation delay	~6.1 ns
Maximum input voltage	300 V _{RMS} CAT II

Physical characteristics

Cable length	1.3 m (4.2 ft)
--------------	----------------

EMC, environment, and safety

Temperature range	
Operating	10 °C to +55 °C (14 °F to 131 °F)
Nonoperating	-51 °C to +71 °C (-60 °F to 160 °F)
Operating and nonoperating	5% to 95% relative humidity (%RH) up to 30 °C (86 °F), 5% to 65% RH above +30 °C (86 °F) up to +55 °C (131 °F)
Altitude	
Operating	<3.0 km (9,842 ft)
Nonoperating	<12.2 km (40,026 ft)

Ordering information

Models

TPP0051 For use with BNC oscilloscopes with 1 M Ω , 20 pF inputs

Standard accessories

003-1433-xx	Adjustment tool
013-0362-xx	Retractable hook tip
016-0633-xx	Color bands, 5 pairs
016-2028-xx	Long ground spring, 2 each
196-3521-xx	6 in. alligator ground lead

Warranty

One-year warranty covering all parts and labor.

Recommended accessories

013-0363-xx	Micro hook tip
013-0366-xx	Universal IC cap
013-0367-xx	BNC-to-probe tip adapter, unterminated
016-2016-xx	PCB-to-probe tip adapter, 10-pack
016-2034-xx	Short ground spring, 2 each
020-3045-xx	Wire, 32 AWG spool
131-8831-xx	Compact probe-tip chassis mount
196-3198-xx	6 in. clip-on ground lead with 0.025 in. pin receptacle
196-3512-xx	12 in. alligator ground
206-0569-xx	MicroCKT test tip



Tektronix is ISO 14001:2015 and ISO 9001:2015 certified by DEKRA.

ASEAN / Australasia (65) 6356 3900
 Belgium 00800 2255 4835*
 Central East Europe and the Baltics +41 52 675 3777
 Finland +41 52 675 3777
 Hong Kong 400 820 5835
 Japan 81 (120) 441 046
 Middle East, Asia, and North Africa +41 52 675 3777
 People's Republic of China 400 820 5835
 Republic of Korea +822 6917 5084, 822 6917 5080
 Spain 00800 2255 4835*
 Taiwan 886 (2) 2656 6688

Austria 00800 2255 4835*
 Brazil +55 (11) 3759 7627
 Central Europe & Greece +41 52 675 3777
 France 00800 2255 4835*
 India 000 800 650 1835
 Luxembourg +41 52 675 3777
 The Netherlands 00800 2255 4835*
 Poland +41 52 675 3777
 Russia & CIS +7 (495) 6647564
 Sweden 00800 2255 4835*
 United Kingdom & Ireland 00800 2255 4835*

Balkans, Israel, South Africa and other ISE Countries +41 52 675 3777
 Canada 1 800 833 9200
 Denmark +45 80 88 1401
 Germany 00800 2255 4835*
 Italy 00800 2255 4835*
 Mexico, Central/South America & Caribbean 52 (55) 56 04 50 90
 Norway 800 16098
 Portugal 80 08 12370
 South Africa +41 52 675 3777
 Switzerland 00800 2255 4835*
 USA 1 800 833 9200

* European toll-free number. If not accessible, call: +41 52 675 3777

For Further Information. Tektronix maintains a comprehensive, constantly expanding collection of application notes, technical briefs and other resources to help engineers working on the cutting edge of technology. Please visit www.tek.com.

Copyright © Tektronix, Inc. All rights reserved. Tektronix products are covered by U.S. and foreign patents, issued and pending. Information in this publication supersedes that in all previously published material. Specification and price change privileges reserved. TEKTRONIX and TEK are registered trademarks of Tektronix, Inc. All other trade names referenced are the service marks, trademarks, or registered trademarks of their respective companies.